

# WIREWORLD MPC 04-2010

MODEL	OPIS	CIJENA (kn)		
<b>Interkonekcijski kabele (RCA-RCA ili XLR-XLR)</b>		<b>0.5M</b>	<b>1.0M</b>	
<b>Terra 52</b>	OFC conductors, high-density polyethylene insulation, gold/nickel/brass contacts			110
<b>Luna 6</b>	OFC conductors, composite insulation, gold / silver / OFC contacts	210		240
<b>Solstice 6</b>	silver plated OFC conductors, composite insulation, gold / silver / OFC contacts	320		380
<b>Oasis 6</b>	OFC conductors, composite insulation, silver-clad OFC contacts	540		700
<b>Equinox 6</b>	Continuous Cast copper conductors, composite insulation, silver-clad OFC contacts	830		1280
<b>Eclipse 6</b>	Continuous Cast copper conductors, composite insulation, silver-clad OFC contacts	2080		2870
<b>Silver Eclipse 6</b>	Continuous Cast silver-clad copper, composite insulation, silver-clad OFC contacts	2870		4470
<b>Gold Eclipse 6</b>	Continuous Cast solid silver conductors, composite insulation, silver-clad OFC contacts	5220		9280
<b>Platinum Eclipse</b>	Continuous Cast solid silver conductors, composite insulation, silver-clad OFC contacts	9860		17400
<b>Zvučnički kabele (terminirano - vilice ili banane)</b>		<b>2.0M</b>	<b>2.5M</b>	<b>3.0M</b>
<b>Horizon 52</b>	2 flat oxygen-free copper conductors, TPE insulation, 16ga./1.25mm <sup>2</sup>	420	450	470
<b>Stream 16/2</b>	2 flat oxygen-free copper conductors, HDPE insulation, 16ga./1.25mm <sup>2</sup>	510	540	580
<b>Luna 16/4</b>	4 flat oxygen-free copper conductors, HDPE insulation, 13ga./2.5mm <sup>2</sup>	650	700	750
<b>Orbit 16/4</b>	4 flat silver-clad OFC conductors, HDPE insulation, 13ga./2.5mm <sup>2</sup>	830	930	1020
<b>Solstice 6</b>	4 flat oxygen-free copper conductors, HDPE insulation, 12ga./3.5mm <sup>2</sup>	1440	1600	1760
<b>Oasis 6</b>	4 flat oxygen-free copper conductors, HDPE insulation, 10ga./4.6mm <sup>2</sup>	1820	2070	2330
<b>Equinox 6</b>	4 flat OCC copper conductors, HDPE insulation, 12ga./3.5mm <sup>2</sup>	3860	4630	5390
<b>Eclipse 6</b>	12 flat OCC copper conductors, HDPE insulation, 10ga./4.6mm <sup>2</sup>	7210	8610	9990
<b>Silver Eclipse 6</b>	12 flat OCC silver-clad conductors, HDPE insulation, 10ga./4.6mm <sup>2</sup>	11660	14200	16760
<b>Gold Eclipse 6</b>	12 flat OCC solid silver conductors, HDPE insulation, 10ga./4.6mm <sup>2</sup>	40890	50750	60600
<b>Platinum Eclipse</b>	18 flat OCC solid silver conductors, HDPE insulation, 9ga./5.4mm <sup>2</sup>	76560	95120	1E+05
<b>Naponski kabele (terminirano - EU Schuko i IEC 15A)</b>		<b>1.0M</b>	<b>2.0M</b>	<b>3.0M</b>
<b>Stratus 52</b>	Oxygen-free copper conductors, 12ga./3mm <sup>2</sup>	450	640	830
<b>Aurora 52</b>	Silver-clad OFC conductors, 12ga./3mm <sup>2</sup>	830	1210	1600
<b>Electra 52</b>	OCC copper conductors, 12ga./3mm <sup>2</sup>	1500	2300	3090
<b>Silver Electra 52</b>	OCC silver-clad copper conductors, 12ga./3mm <sup>2</sup>	2870	4470	6060
<b>Gold Electra 52</b>	OCC solid silver conductors, 12ga./3mm <sup>2</sup>	6960	12760	18560
<b>MATRIX</b>	rack mount, shielded power cord extender		770	
<b>Digitalni kabele (Coax / 75-ohm / RCA ili BNC)</b>		<b>0.5M</b>	<b>1.0M</b>	<b>1.5M</b>
<b>Chroma 5</b>	Oxygen-Free Copper, polyethylene foam, gold / silver / OFC contacts	120	130	140
<b>Ultraviolet 5</b>	Silver-plated OFC, polyethylene foam, gold / silver / OFC contacts	200	220	250
<b>Starlight 6</b>	Silver-clad OCC & OFC, composite, silver-clad OFC contacts	380	510	640
<b>Silver Starlight 6</b>	OCC silver-clad copper, composite, silver-clad OFC contacts	1280	1590	1920
<b>Gold Starlight 6</b>	OCC solid silver, composite, silver-clad OFC contacts	2080	3190	4310
<b>Platinum Starlight</b>	OCC solid silver, composite, silver-clad OFC contacts	4930	8700	12470
<b>Digitalni kabele (Balansirani / 110-ohm / AES-EBU)</b>		<b>0.5M</b>	<b>1.0M</b>	<b>1.5M</b>
<b>Oasis 6</b>	Oxygen-Free Copper conductors, composite insulation	280	350	440
<b>Starlight 6</b>	OCC Copper conductors, composite insulation	420	640	860
<b>Gold Starlight 5</b>	OCC solid silver conductors, microporous Teflon insulation	1590	2550	3510
<b>Platinum Starlight</b>	OCC solid silver conductors, composite insulation	4930	8700	12470
<b>Digitalni kabele (Optički / Toslink / Glass Toslink)</b>		<b>0.5M</b>	<b>1.0M</b>	<b>2.0M</b>
<b>NOVA 6</b>	PMMA monofilament, Toslink		260	320
<b>Supernova 6</b>	280 glass fibers	860	960	1150
<b>USB Digitalni kabele (USB A - B / USB A - mini B)</b>		<b>0.5M</b>	<b>1.0M</b>	<b>2.0M</b>
<b>Ultraviolet</b>	Silver-plated Oxygen-Free Copper	290	320	380
<b>Starlight</b>	Silver-plated Oxygen-Free Copper	570	640	770
<b>HDMI kabele (verzija 1.4a - Full 3D HD kompatibilan)</b>		<b>0.5M</b>	<b>1.0M</b>	<b>2.0M</b>
<b>Island 6</b>	16 copper conductors, High speed with Ethernet	190	220	270
<b>Chroma 6</b>	16 OFC conductors, High speed with Ethernet	320	380	450
<b>Ultraviolet 6</b>	16 silver-plated OFC conductors, High speed with Ethernet		770	930
<b>Starlight 6</b>	16 silver-clad OFC conductors, High speed with Ethernet		1280	1590
<b>Silver Starlight 6</b>	24 silver-clad OFC conductors, High speed with Ethernet	1850	2230	3030
<b>Platinum Starlight</b>	24 solid silver conductors, High speed with Ethernet	4060	5800	8700